

# SL/Chips

## Epokate flooring solution

# Eposyst SL/Chips

Pigmented two-component solvent-free epoxy resin flooring system with lightly scattered of colour chips

### Eposyst SL/Chips

#### uses

- normal wear production sites
- storage rooms
- exhibition halls
- offices
- corridors
- garages
- agricultural facilities

### Eposyst SL/Chips

#### characteristics/advantages

- good wear resistance
- good mechanical resistance
- good chemical resistance
- lightly slip resistance
- decorative, a wide range of colors
- solvent free with minimal odour
- seamless, enabling easy maintenance
- easy flow, selflevelling properties

### Eposyst SL/Chips

#### technical properties

bond strength:	≥1,5 N/mm <sup>2</sup> (EN 1542)
abrasion resistance:	≥3000 mg (EN ISO 5470-1)
water permeability:	w < 0,1 kg/m <sup>2</sup> x h <sup>0,5</sup> (EN 1062-3)
impact resistance:	≥13 Nm (EN ISO 6272)
flexural strength:	≥10 N/mm <sup>2</sup> (EN ISO 178)
slip resistance:	R9 (DIN 51130)
FeRFA:	type 5


Containing materials meet the requirements of CE and standards: EN 13813 ja EN 1504-2



### Eposyst SL/Chips

#### flooring solution description

Total thickness:  
1,5-3,0 mm



❶ Priming	EPOKATE KRUNT
Scattering	quarz sand 0,1-0,3 mm
❷ Levelling coating	EPOKATE SL
Filler	quarz sand 0,1-0,3 mm
Decorative scatter	Disboxid Multicolor chips

#### Available basic colours:

